Honeywell | Ceiling Fans



APPLICATION:

- Indoor
- Middle Room (up to 12x12)

BENEFITS:

- Energy efficiency.
- Improved environmental performance.Ability to operate in cold conditions.
- No heat or uv emissions.
- Design flexibility.
- Long lifespan.



| AV | AILABLE OPTIO | NS: | | | |
|------|---|-----------------------|---------|--|--|
| HW | -F33-BN | Brushed Nickel | | | |
| Also | Available in: | Oil Rubbed Bronze | | | |
| | | | | | |
| SPI | ECIFICATIONS | | | | |
| Wat | tts (High): | 45 | | | |
| Size |): | 42" | | | |
| Mot | tor Finish: | Metal | | | |
| Mot | tor Finish: | Iron + Copper (153*13 | 0*10mm) | | |
| EN | ERGY INFORMA | TION | | | |
| Airf | Airflow (CFM) when operated at high speed: | | 4050 | | |
| Airf | Airflow (CFM): | | 2835 | | |
| RPN | И (High): | | 188 | | |
| Amı | p (High): | | 0.38 | | |
| For | For more information, please visit www.HoneywellLights-fans.com | | | | |

| ADDITIONAL INFORMATION | | | |
|------------------------|-------------------------|--|--|
| Blades: | MDF Blades | | |
| Blade Pitch : | 12° | | |
| Installation: | Hugger | | |
| Down Rod: | No | | |
| Max Ceiling Angle: | 18° | | |
| Lead Wire: | 20" | | |
| Reverse Airflow: | Yes | | |
| | | | |
| Number of Lamps: | 2 | | |
| Light Bulb Usage: | E27 Base (not included) | | |
| Capacitor: | 4/280V+5+6UF/250V | | |
| Control: | Pull chain | | |
| Switch Housing Cap: | Included | | |
| | | | |

Iluminaciones Técnicas S.A.

Panama Headquarters 1 (888) 502-8432 Email: info@HoneywellLights-fans.com www.HoneywellLights-fans.com

The Honeywell trademark is used under license from Honeywell International Inc.
Honeywell makes no representations or warranties with respect to this product. Manufactured by Iluminaciones Técnicas S.A.