Honeywell | LED Panel





(CCT) Color Temperature Switch



AVAILABLE WATTAGE OPTIONS:


- 18W-CCT Switchable
- 24W-CCT Switchable

BENEFITS:

- · Energy efficiency.
- · Improved environmental performance.
- Ability to operate in cold conditions.
- · No heat or uv emissions.
- · Design flexibility.
- Instant lighting and the ability to withstand frequent switching.
- Long lifespan.
- General lighting for limited build-in height.

APPLICATION:

- Office Building.
- Retail.
- Indoors.



SPECIFICATIONS		
Shape:	Round LED Lamp	
Cap/Fitting:	Recessed Ceiling	
F:-:	AA/I.:	

ADDITIONAL	ADDITIONAL INFORMATION		
Volt	100-240V / 50-60Hz		
Beam Angle:	110°		

1 1111011.	Willes								
AVAILAB	AVAILABLE WATTAGE OPTIONS								
Power	Tone	Brightness	Size	Dimmable / Non Dimmable	Model				
18W	3000K/4000K/6500K	1430 Lm/1580 Lm/1430 Lm	D-220mm H-18mm	Non Dimmable	HW-P05-R18W-CCT				
24W	3000K/4000K/6500K	1730 Lm/1900 Lm/1730 Lm	D-292mm H-18mm	Non Dimmable	HW-P05-R24W-CCT				

For more information, please visit www.HoneywellLights-fans.com

Iluminaciones Técnicas S.A.

Panama Headquarters 1 (888) 502-8432 Email: info@HoneywellLights-fans.com www.HoneywellLights-fans.com ©2022 ILUMINACIONES TECNICAS S.A. All rights reserved.

The Honeywell trademark is used under license from Honeywell International Inc.

 $Honey well\ makes\ no\ representations\ or\ warranties\ with\ respect\ to\ this\ product.\ Manufactured\ by\ Iluminaciones\ T\'ecnicas\ S.A.$