

LED PANEL LIGHT

HW-P2X2-04-PS-CCT-UL



Indoor

Backlite panel UL Certified, with high uniform lighting performance. watt and CCT selectable

FEATURES

- ANSI C82.77-2002 Surge Protector
- THD < 20%
- Excellent surface treatment
- Light in weight and more like traditional grille light, better for user experience.
- Backlit design without LGP, No risk of yellowing.
- Fully Automated production lines guarantees short lead time.
- 3 CCT Selectable: 3500K, 4000K, 5000K could be adjusted with a switch

APPLICATION

- Classroom
- Office
- Meeting Room
- Shopping Mall
- Commercial Areas
- And others



RoHS




Multi Color Temperature (CCT)






Multi Wattage Switchable

OPTICAL DATA		PHYSICAL DATA		ELECTRICAL DATA	
Color Temperature (CCT)	3500K, 4000K, 5000K	Finish	White	Input Power	20W, 30W, 35W
CCT Switchable	YES	Protection Level - IP	IP20	Power Switchable	YES
Luminous Flux	3240/4490/5330 lm	Dimensions (LxWxH)	604x604x38mm	Operating Voltage	120-277 V
Type of Distribution	Direct Symmetrical	Type of Installation	Recessed or Hanging	Frequency	50-60 Hz
Beam Angle	120°	Body Frame	Aluminium	Power Rating	>0.90
Efficiency	110 Lm/W	Optical Material	Diffuser PC	CRI	80
Life Span	50 000 Hrs	Operation Temperature	-20°C to +40°C	Dimmable	0-10V

DIMENSIONS



This panel can be installed in two different ways: hanging or recessed.



LUMINOUS INTENSITY DISTRIBUTION

