

LED FLOODLIGHT SOLAR

HW-SFL-01



LED luminaire for street and outdoor lighting, modern and compact design, uniform light projection, high efficiency, long life and easy installation, reduces energy consumption and maintenance costs.

FEATURES

- Heavy Duty Die Cast aluminum housing with ample heat sinking.
- LED fixture whit bracket can adjustable in 0-270 degrees.
- Control Remote Included
- Slipfit Arm included
- IP65/IK08.
Long Lifespan.

APPLICATION

- Park
- Square
- Trails
- Residential buildings
- Parking lot
- Bridges

CE IP65



SPECIFICATIONS

Model	Power	Lumen	Solar Panel	Charging Time	Battery Power
HW-SFL-01-25W-3K	25 W	162 Lm/W	8W / 6V	5 Hrs	6000 mAh
HW-SFL-01-25W-6K	25 W	162 Lm/W	8W / 6V	5 Hrs	6000 mAh
HW-SFL-01-60W-6K	60 W	162 Lm/W	20W / 6V	6Hrs	21 000 mAh
HW-SFL-01-100W-6K	100 W	162 Lm/W	30W / 9V	5Hrs	24 000 mAh
HW-SFL-01-200W-3K	200 W	162 Lm/W	35W / 9V	4 Hrs	30 000 mAh
HW-SFL-01-300W-6K	300 W	162 Lm/W	35W / 9V	5 Hrs	36 000 mAh

OPTICAL DATA

Color Temperature (CCT)	3000K or 6000K
Beam Angle	110°
Type of Distribution	Direct Symmetrical
Life Span	50 000 H

PHYSICAL DATA


Finish	Grey
Protection Level - IP	IP65
Body Frame	Aluminium + ABS
Optical Material	Diffuser PC
Operation Temperature	0°C to +50°C

ELECTRICAL DATA

Control Remote Included	YES
Rechargeable battery	LiFePO4
RA	70
Dimmable	NO

DIMENSIONS

Model	Size (LxWxH)
HW-SFL-01-25W-3K	163x50x185mm
HW-SFL-01-25W-6K	163x50x185mm
HW-SFL-01-60W-6K	204x55x237mm
HW-SFL-01-100W-6K	250x55x290mm
HW-SFL-01-200W-6K	250x55x290mm
HW-SFL-01-300W-6K	250x55x290mm



LUMINOUS INTENSITY DISTRIBUTION

