LED STREET LIGHT

HW-ST-01-PS-CCT



LED luminaire for street and outdoor lighting, modern and compact design, uniform light projection, high efficiency, long life and easy installation, reduces energy consumption and maintenance costs.

FEATURES

- . Heavy Duty Die Cast aluminum housing with ample heat sinking.
- Angle of inclination adjustable in ±90.
- Slipfit Arm included
- . IP65/IK08/4KV Rating.
- . Long Lifespan.

APPLICATION

- Park
- Public or Private roads
- Residential buildings

- Square Trails
- Parking lot Bridges
- And others



PHOTOCELL SENSOR



Multi Color **Temperature** (CCT)



Multi Wattage **Switchable**






Water **Proof**

OPTICAL DATA	
Color Temperature (CCT)	4000K,5000K,6000K
Lumens	16,856 lm/24,359 lm/30,455 lm
Beam Angle	80x150° Type III
Type of Distribution	Direct Symmetrical
Life Span	50 000 H
Optical Material	Diffuser PC

PHYSICAL DATA	
Finish	Dark Bronze
Protection Level-IP	IP65
Dimensions (LxWxH)	300x438x62mm
Body Frame	Die-Cast Aluminium
Weight	5.22 kg
Operation Temperature	-40°C to +50°C

ELECTRICAL DATA		
Input Power	100W, 150W, 200W	
Power Switchable	YES	
Operating Voltage	120-277 V	
Frequency	50-60 Hz	
Power Factor	>0.95	
CRI	70	

DIMENSIONS








Power Selectable Switch





(CCT) Color Temperature Switch





LUMINOUS INTENSITY DISTRIBUTION

