

LED TRI-PROOF LIGHT

HW-TRI-01-PS-65K



Hermetic industrial luminaire, clipless design, smooth and elegant appearance, no need to open the diffuser to connect with safe and reliable protection level
Switchable power: 30W, 40W or 50W.

FEATURES

- UV protection
- Built in high luminous efficiency LED Chip and Driver
- IP65/IK08
- 3 Level Power Switchable
- Fast connection
- Light Efficiency: 100-118lm/W

APPLICATION

- Industrial Areas
- Schools
- Sidewalks
- And Others
- Parks



LED



Multi Wattage Switchable



Eco Friendly

UV Protection



Easy Installation

OPTICAL DATA		PHYSICAL DATA		ELECTRICAL DATA	
Color Temperature (CCT)	6500 K	Finish	Gray & White	Input Power	30W, 40W, 50W
Luminous Flux	3540, 4280, 5170 Lm	Protection Level - IP	IP65	Power Switchable	YES
Beam Angle	120°	Dimensions (LxWxH)	1200x70x56 mm	Operating Voltage	100-277 V
Type of Distribution	Direct Symmetrical	Type of Installation	Surface Mounted	Frequency	50-60 Hz
Opening Angle	80	Body Frame	PC	Power Factor	>0.9
Efficiency	100-118 Lm/W	Optical Material	Diffuser PC	CRI	80
		Operation Temperature	-20°C to +40°C	Dimmable	NO

DIMENSIONS



W - 70mm




H - 56mm

L - 1200mm



30W 40W 50W



Power Selectable Switch

LUMINOUS INTENSITY DISTRIBUTION

