



FULTON

APPLICATION:

- Indoor
- Large Room (up to 15' X 15')

BENEFITS:

- Improved environmental performance.
- Ability to operate in cold conditions.
- No heat or uv emissions.
- Design flexibility.
- Long lifespan.

CERTIFICATE:



AVAILABLE OPTIONS:

HW-F-03-SN Brushed Nickel

Also Available in: White

SPECIFICATIONS

Watts (High): 54W

Volt: 100-130V

Size: 52"

Motor Finish: Silicon Steel + Copper Wire

Motor Size: AC 153*15mm

ENERGY INFORMATION

Airflow (CFM) when operated at high speed: 4580

Airflow (CFM): 3204

RPM (High): 215

ADDITIONAL INFORMATION

Blades: Plywood

Reverse Airflow: Yes

Installation: Tri-Mount

Down Rod: 5" + 10"

Max Ceiling Angle: 18°

Certification: ETL

LIGHT SOURCE

Light Usage: LED

Wattage: 15W

Control: 3 Speed Remote Control

For more information, please visit www.HoneywellLights-fans.com

Iluminaciones Técnicas S.A.

Panama Headquarters 1 (888) 502-8432

Email: info@HoneywellLights-fans.com

www.HoneywellLights-fans.com

©2025 ILUMINACIONES TECNICAS S.A. All rights reserved.

The Honeywell trademark is used under license from Honeywell International Inc.

Honeywell makes no representations or warranties with respect to this product. Manufactured by Iluminaciones Técnicas S.A.

SPEC302 | 01-2025