



LED LIGHTBULB GU10 / 2-PIN TWIST AND LOCK

LUMINOUS INTENSITY DISTRIBUTION CURVE



AVAILABLE WATTAGE OPTIONS:


- 5W
- 7W
- 5W-DIM

BENEFITS:

- Energy efficiency.
- No visible flickering.
- Color consistency over long lifespan.
- Improved environmental performance.
- Ability to operate in cold conditions.
- No heat or UV emissions.
- Design flexibility.
- Instant lighting and the ability to withstand frequent switching.

APPLICATION:

- For use in mains voltage GU10 downlights, spotlights and luminaires.



SPECIFICATIONS	
Shape:	GU10
Cap/Fitting:	GU10
Certification:	CE
Beam Angle:	38° Degree
Material:	Heat dissipating thermoplastic body.

DIMENSION			
Height:	54 mm	Height Bulb Pro:	55 mm
Diameter:	50 mm	Diameter Bulb Pro:	50 mm

ADDITIONAL INFORMATION	
Equivalent:	50W Halogen GU10
Certifications:	BGU10-01,02,03,04,05: CE BGU10-06: UL, FC, RoHS

AVAILABLE WATTAGE OPTIONS					
Power	Tone	Brightness	Volt	Dimmable / Non Dimmable	Model
5W	3000K	410 Lm	100-240V - 50-60Hz	Non Dimmable	HW BGU10 01 2PK 5W 3K
5W	4000K	470 Lm	100-240V - 50-60Hz	Non Dimmable	HW-BGU10-01-2PK-5W-4K
5W	6500K	470 Lm	100-240V - 50-60Hz	Non Dimmable	HW-BGU10-01-2PK-5W-6K
5W	3000K	460 Lm	100-130V - 50-60Hz	Dimmable	HW-BGU10-03-2PK-5W-DIM3K
5W	4000K	450 Lm	100-130V - 50-60Hz	Dimmable	HW-BGU10-03-2PK-5W-DIM4K
5W	6500K	460 Lm	100-130V - 50-60Hz	Dimmable	HW-BGU10-03-2PK-5W-DIM6K
6.5W	4000K	700 Lm	100-120V-50-60Hz	Dimmable	HW-BGU10-06-UL-2PK-6.5W-DIM4K
7W	3000K	640 Lm	100-240V - 50-60Hz	Non Dimmable	HW-BGU10-02-2PK-7W-3K
7W	4000K	650 Lm	100-240V - 50-60Hz	Non Dimmable	HW-BGU10-02-2PK-7W-4K
7W	6500K	650 Lm	100-240V - 50-60Hz	Non Dimmable	HW-BGU10-02-2PK-7W-6K
7W	3000K	900 Lm	100-277V-50-60Hz	Non Dimmable	HW-BGU10-04PRO-2PK-7W-3K
7W	3000K	800 Lm	100-130V-50-60Hz	Dimmable	HW-BGU10-05PRO-2PK-7W-3K-DIM3K

For more information please visit www.HoneywellLights-fans.com